

PowerConneX Product Specification

Series: Basic PDU



Durable outlet surface made of high quality PC-ABS, LED Master Switch with protection cover



Socket legs are Nickel coated copper for reducing electric arc when plugging



Industrial grade Copper bar welded for maximum power output with no wiring between outlets



Light weight of industrial grade aluminum alloy case with rust proof



Molded PVC Insulation between copper bar and aluminum alloy case preventing short circuit and leakage current



IEC60906 plug (NEMA 5-15P 15A)

1

2

3

4

5

DIMENSION (Unit: mm)			FibreConneX Limited.	
Length:	482	Mounting length:	465	Product Name 6 x Universal outlet, with overload protection, LED power Indicator and master switch, Cable 3M
Width:	44.4	Case length:	430.8	
Height:	44.4			Part Number PXE2250W4-06AHMTMB

PowerConneX Product Specification

Series: Basic PDU

Product Description 6 x Universal outlet, with overload protection, LED power Indicator and master switch, Cable 3M

Part Number PXE2250W4-06AHMTMB

NO.	Item	Detailed Description
1	Product Series	PXE2250 Series
2	Socket Type	GB2099.3 Socket
3	Socket Quantity	6 Way
4	Power Input	Left end single input
5	Bracket Install	Frontal installation (1U)
6	Cable with plug	IEC60906 plug (NEMA 5-15P 15A)
7	Protection Function / Control Function	illuminated master switched & Overload protector and indicator
8	Case	Black
9	Cable Specification	3 x 16AWG x 3M
10	Product Size	L x W x H = 482 x 44.4 x 44.4 mm
11	Mounting Length	465 mm
12	Case Length	430.8 mm
13	PDU Exponent	1.238
14	Fittings	Cage Nut
15	Rating voltage	220-250VAC 50/60Hz
16	Rating Current	15A
17	Max. Power	3750W
18	Safety Authentication	
19	RoHS Compliance	Yes