

PowerConneX Product Specification

Series: Basic PDU



Master Circuit Breaker for maximum protection with durable outlet surface made of PC-ABS



Socket legs are Nickel coated copper for reducing electric arc when plugging



Industrial grade Copper bar welded for maximum power output with no wiring between outlets



Light weight of industrial grade aluminum alloy case with rust proof



Molded PVC Insulation between copper bar and aluminum alloy case preventing short circuit and leakage current



IEC60906 plug (NEMA 5-15P 15A)

1

2

3

4

5

DIMENSION AND TOLERANCES (Unit: mm)				FibreConneX Limited.	
Length:	838.6	Mounting length:	812.1	Product Name	12 x Universal outlet, with MCB 16A & LED power Indicator, Cable 3M
Width:	44.4	Case length:	785.6	Part Number	PXE2250W4-12AVMRMB
Height:	44.4				

PowerConneX Product Specification

Series: Basic PDU

Product Description 12 x Universal outlet, with MCB 16A & LED power Indicator, Cable 3M

Part Number PXE2250W4-12AVMRMB

NO.	Item	Detailed Description
1	Product Series	PXE2250 Series
2	Socket Type	GB2099.3 Socket
3	Socket Quantity	12 Way
4	Power Input	Left end single input
5	Bracket Install	Frontal installation (1U)
6	Cable with plug	IEC60906 plug (NEMA 5-15P 15A)
7	Protection Function / Control Function	16A Master air circuit breaker and LED indicator
8	Case	Black
9	Cable Specification	3 x 16AWG x 3M
10	Product Size	L x W x H = 838.6 x 44.4 x 44.4 mm
11	Mounting Length	812.1 mm
12	Case Length	785.6 mm
13	PDU Exponent	2.028
14	Fittings	Cage Nut
15	Rating voltage	220-250VAC 50/60Hz
16	Rating Current	15A
17	Max. Power	3750W
18	Safety Authentication	
19	RoHS Compliance	Yes